

ROSSERHEAD DEBARKER DIMENSIONS AND SPECIFICATIONS

- OPTIONS:**
1. Overall size may be shortened or lengthened for specific needs.
 2. All steel insulated operators cab, with lights, heater and air conditioning. (Stand Alone Cab)
 3. Diesel powered units are available.
 4. Export models may have motors for 380/3/50 operation.
 5. Additional hydraulic power may be supplied for live decks or hydraulic kickers.
 6. Barking head size may be increased or decreased for specific needs.
 7. Precision Bark Conveyor may be included as part of debarking frame.



P848H with optional cab

Better Engineered, Built Heavier and Stronger for Low Cost, Low Maintenance, Clean Debarking.

DEBARKER SPECIFICATIONS

Debarker Model	P-636-S	P-636-H	P-742-H	P-742-XH	P-848-S	P-848-H
Barking Head	12" Dia. X 12" Wide	12" Dia. X 12" Wide	12" Dia. X 12" Wide	12" Dia. X 12" Wide	15" Dia. X 16" Wide	15" Dia. X 16" Wide
Debarker Motor	30 HP	30 HP	30 HP	30 HP	50 HP	50 HP
Range of Log Lengths	8' to 20'	8' to 20'	8' to 20'	8' to 20'	8' to 20'	8' to 20'
Log Passed	25'	25'	25'	25'	25'	25'
Range of Log Diameters	6" to 36"	6" to 36"	7" to 42"	7" to 42"	8" to 48"	8" to 48"
Log Kicker Arms	5	5	5	5	5	5
Log Kicker Cylinder Dia.	1-3 ¹ / ₂ " HYD	1-3 ¹ / ₂ " HYD	2-3 ¹ / ₂ " HYD	2-3 ¹ / ₂ " HYD	2-3 ¹ / ₂ " HYD	2-3 ¹ / ₂ " HYD
Log Rotation Rolls	6 Sets	6 Sets	6 Sets	6 Sets	6 Sets	6 Sets
Rotation Roll Shaft Size	2 ⁷ / ₁₆ "	2 ⁷ / ₁₆ "	3 ⁷ / ₁₆ "	3 ⁷ / ₁₆ "	3 ⁷ / ₁₆ "	4 ⁷ / ₁₆ "
Hydraulic System Motor	25 HP	25 HP	25 HP	25 HP	25 HP	25 HP
Variable Speed	Yes	Yes	Yes	Yes	Yes	Yes
Machine Dim. Width*	6'-11"	6'-11"	6'-11"	6'-11"	7'-5"	7'-5"
Machine Dim. Length	33'-0"	33'-0"	33'-0"	33'-0"	35'-0"	35'-0"
Machine Dim. Height	8'-1"	8'-1"	8'-1"	8'-1"	8'-1"	8'-1"
Carriage Overhang	1'-3"	1'-3"	1'-6"	1'-6"	1'-6"	1'-6"
Machine Weight	12,000 Lbs.	12,500 Lbs.	15,000 Lbs.	15,800 Lbs.	16,400 Lbs.	17,600 Lbs.

PRECISION HUSKY 

C O R P O R A T I O N

P.O. DRAWER 507 • LEEDS, AL 35094-0507 • 205/640-5181 • FAX 205/640-1147

EMAIL: precisionhusky@msn.com • WEB SITE: www.precisionhusky.com

